

PRODUCT-DETAILS

MP1-11R

MP1-11R Pushbutton



General Information

Extended Product Type	MP1-11R
Product ID	1SFA611100R1101
EAN	7320500261057
Catalog Description	MP1-11R Pushbutton

Long Description	The MP1-11R Pushbutton is: Momentary - Flush - Red - Illuminated - Black Plastic - No contact block
	This Pushbutton is part of ABB's modular plastic range, the most versatile range with a high level of flexibility and market-leading electrical ratings. Engineered for total reliability, longer lifetime, and highest mechanical durability. Self-cleaning contacts ensure reliable operation without the need for maintenance, increasing uptime. A high degree of protection guarantees reliability in extreme environments. The innovative design simplifies the entire process, from selection to easy and quick, tool-free installation. The perfect solution for every application.

Ordering

Minimum Order Quantity	10 piece
Customs Tariff Number	8536501999

Popular Downloads

Data Sheet, Technical Information	1SFC151007C02__
Instructions and Manuals	1SFC151011M0201

Dimensions

Product Net Width	0.029 m
Product Net Height	0.029 m
Product Net Depth / Length	0.033 m
Product Net Weight	0.011 kg

Technical

Ambient Air Temperature	Operation -25 ... +70 °C Storage -40 ... +85 °C
Color	Red
Actuator Type	Flush
Bezel Material	Black Plastic
Illumination	Illuminated
Function	Momentary
Degree of Protection	Front IP66
Enclosure Type NEMA	Type1 Type12 Type13 Type3R Type4 Type4X
Mechanical Durability	2 million

Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	0635 4
RoHS Information	2CMT2015-005452
WEEE Category	Product Not in WEEE Scope

Certificates and Declarations (Document Number)

cULus Certificate	9AKK107046A9925
Declaration of Conformity - CE	2CMT2015-005452
DNV GL Certificate	E-14107
Environmental Information	1SAC200079H0001
Instructions and Manuals	1SFC151011M0201
REACH Declaration	2CMT2022-006479
RoHS Information	2CMT2015-005452

Container Information

Package Level 1 Units	bag 1 piece
Package Level 1 Width	0.135 m
Package Level 1 Depth / Length	0.145 m
Package Level 1 Height	0.035 m
Package Level 1 Gross Weight	0.014 kg
Package Level 1 EAN	7320500261057

Classifications

Object Classification Code	S
ETIM 6	EC000221 - Front element for push button
ETIM 7	EC000221 - Front element for push button
ETIM 8	EC000221 - Front element for push button
eClass	V11.0 : 27371210
UNSPSC	39121500

IDEA Granular Category Code (IGCC)	5212 >> Push button for distribution board
E-Number (Finland)	2313656
E-Number (Norway)	4372051
E-Number (Sweden)	3715201

Categories

Low Voltage Products and Systems → Control Products → Pilot Devices → Modular Plastic Range



PRODUCT-DETAILS

MP1-11G

MP1-11G Pushbutton



General Information

Extended Product Type	MP1-11G
Product ID	1SFA611100R1102
EAN	7320500261064
Catalog Description	MP1-11G Pushbutton
Long Description	<p>The MP1-11G Pushbutton is: Momentary - Flush - Green - Illuminated - Black Plastic - No contact block</p> <p>This Pushbutton is part of ABB's modular plastic range, the most versatile range with a high level of flexibility and market-leading electrical ratings. Engineered for total reliability, longer lifetime, and highest mechanical durability. Self-cleaning contacts ensure reliable operation without the need for maintenance, increasing uptime. A high degree of protection guarantees reliability in extreme environments. The innovative design simplifies the entire process, from selection to easy and quick, tool-free installation. The perfect solution for every application.</p>

Ordering

Minimum Order Quantity	10 piece
Customs Tariff Number	8536501999

Popular Downloads

Data Sheet, Technical Information	1SFC151007C02_
Instructions and Manuals	1SFC151011M0201

Dimensions

Product Net Width	0.029 m
Product Net Height	0.029 m
Product Net Depth / Length	0.033 m
Product Net Weight	0.011 kg

Technical

Ambient Air Temperature	Operation -25 ... +70 °C Storage -40 ... +85 °C
Color	Green
Actuator Type	Flush
Bezel Material	Black Plastic
Illumination	Illuminated
Function	Momentary
Degree of Protection	Front IP66
Enclosure Type NEMA	Type1 Type12 Type13 Type3R Type4 Type4X
Mechanical Durability	2 million

Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	0635 4
RoHS Information	2CMT2015-005452
WEEE Category	Product Not in WEEE Scope

Certificates and Declarations (Document Number)

cULus Certificate	9AKK107046A9925
Declaration of Conformity - CE	2CMT2015-005452
DNV GL Certificate	E-14107
Environmental Information	1SAC200079H0001
Instructions and Manuals	1SFC151011M0201
REACH Declaration	2CMT2022-006479
RoHS Information	2CMT2015-005452

Container Information

Package Level 1 Units	bag 1 piece
Package Level 1 Width	0.135 m
Package Level 1 Depth / Length	0.145 m
Package Level 1 Height	0.035 m
Package Level 1 Gross Weight	0.014 kg
Package Level 1 EAN	7320500261064

Classifications		
Object Classification Code		S
ETIM 6	EC000221 - Front element for push button	
ETIM 7	EC000221 - Front element for push button	
ETIM 8	EC000221 - Front element for push button	
eClass		V11.0 : 27371210
UNSPSC		39121500
IDEA Granular Category Code (IGCC)	5212 >> Push button for distribution board	
E-Number (Finland)		2313658
E-Number (Norway)		4372052
E-Number (Sweden)		3715202

Categories

Low Voltage Products and Systems → Control Products → Pilot Devices → Modular Plastic Range



PRODUCT-DETAILS

MPET4-10R

MPET4-10R Emergency stop



General Information

Extended Product Type	MPET4-10R
Product ID	1SFA611523R1001
EAN	7320500372548
Catalog Description	MPET4-10R Emergency stop
Long Description	<p>The MPET4-10R Emergency stop is: Twist release - Momentary - Mushroom 40 mm - Red - Non-illuminated - No contact block</p> <p>This Emergency stop is part of ABB's modular plastic range, the most versatile range with a high level of flexibility and market-leading electrical ratings. Engineered for total reliability, longer lifetime, and highest mechanical durability. Self-cleaning contacts ensure reliable operation without the need for maintenance, increasing uptime. A high degree of protection guarantees reliability in extreme environments. The innovative design simplifies the entire process, from selection to easy and quick, tool-free installation. The perfect solution for every application.</p>

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85369001

Popular Downloads

Data Sheet, Technical Information	1SFC151007C02_
Instructions and Manuals	1SFC151011M0201

Dimensions

Product Net Width	0.04 m
Product Net Height	0.04 m
Product Net Depth / Length	0.068 m
Product Net Weight	0.036 kg

Technical

Ambient Air Temperature	Operation -25 ... +70 °C Storage -40 ... +85 °C
Color	Red
Actuator Type	Mushroom 40 mm
Bezel Material	n/a
Illumination	Non-illuminated
Function	Maintained
Sub-Function	Twist release
Degree of Protection	Front IP66
Enclosure Type NEMA	Type1 Type12 Type13 Type3R Type4 Type4X

Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	0635 4
RoHS Information	2CMT2015-005444
WEEE Category	Product Not in WEEE Scope

Certificates and Declarations (Document Number)

cULus Certificate	9AKK107046A9925
Declaration of Conformity - CE	2CMT2015-005444
DNV GL Certificate	E-14107
Environmental Information	1SAC200078H0001
Instructions and Manuals	1SFC151011M0201
RoHS Information	2CMT2015-005444

Container Information

Package Level 1 Units	bag 1 piece
Package Level 1 Width	0.135 m
Package Level 1 Depth / Length	0.145 m
Package Level 1 Height	0.045 m
Package Level 1 Gross Weight	0.039 kg
Package Level 1 EAN	7320500372548

Classifications	
Object Classification Code	S
ETIM 6	EC001038 - Front element for mushroom push-button
ETIM 7	EC001038 - Front element for mushroom push-button
ETIM 8	EC001038 - Front element for mushroom push-button
eClass	V11.0 : 27371210
UNSPSC	39121545
IDEA Granular Category Code (IGCC)	5212 >> Push button for distribution board
E-Number (Finland)	2315853
E-Number (Norway)	4372205
E-Number (Sweden)	3705076

Categories

Low Voltage Products and Systems → Control Products → Pilot Devices → Modular Plastic Range

