

Switches 240V~50Hz



289101	10AX, 1Way Switch, 1M	
289102	10AX, 2Way Switch, 1M	
289103	10AX, 1Way Switch with LED Indicator, 1M	
289104	10A, Bell Push Switch, 1M	
289105	10A, Bell Push Switch with LED Indicator, 1M	
289161	20A, 1Way Switch, 1M	
289162	20A, 2Way Switch, 1M	
289163	20A, 1Way Switch with LED Indicator, 1M	

Dura Switches 240V~50Hz



289201	10AX, 1Way Switch, 2M	
289202	10AX, 2Way Switch, 2M	
289203	10AX, 1Way Switch with LED Indicator, 2M	
289204	10A, Bell Push Switch, 2M	
289205	10A, Bell Push Switch with LED Indicator, 2M	
289261	20A, 1Way Switch, 2M	
289262	20A, 2Way Switch, 2M	
289263	20A, 1Way Switch with LED Indicator, 2M	
289232	32A, D.P Switch with LED Indicator, 2M	

Sockets 240V~ 50Hz

289323	10A, 3Pin Uni D Socket, 2M	
289325	10A, Multi Socket, 2M	
289316	16A, 3Pin Round Socket, 2M ISI	
289366	10A/20A, Twin Socket, 2M	
289368	6A/16A, Twin Socket, 2M ISI	
289363	6A/10A/13A, Combi Socket, 2M	
289330	10A, 3Pin Round Socket, 2M, ISI	
289312	10A, 2Pin F/R Socket, 1M	
289313	6A, 2Pin Round Socket (with Shutter),1M, ISI	

Fan Regulator (240V-50Hz)

289510	100W, Fan Regulator, 1M	
289500	100W, Fan Regulator, 2M	
288220	100W, High speed fan regulator, 2M	

Light Dimmer 240V-50Hz

289545	450W, Dimmer, 1M	
289565	650W, Dimmer, 2M	
289566	150W LED Dimmer, 2M	

Ideal for controlling Fan Motors (inductive Loads)

Support Moduler (240V~50Hz)

289677	TV Socket Outlet, 1M	
289666	Cord Outlet with Grip, 1M	
289107	Audio Video Socket, 1M	
289110	3.5mm Audio Jack (female to female connector)	
288219	USB Charger - 1000mA 5V DC, 1M	
289109	USB Charger - 2100mA 5V DC, 1M (CRS Certified)	
289108	USB Charger - 2500mA 5V DC, 2M (CRS Certified)	
289681	Fuse Unit 16 or 10A, 1M	
289684	Blank Plate, 1M	
289688	Night Lamp with LED (Red), 2M	

*16A, 20A, 25A Switch not suggested for geyser load. Instead MCB/Motor Starter must be used


Data Socket

289622	Double RJ-11 Telephone Socket w/o Shutter, 1M	
289611	RJ-11 Telephone Socket with Shutter, 1M	
289655	RJ45 Computer Socket (Cat5), 2M	
289685	RJ45 Computer Socket (Cat6), 1M	
289686	RJ45 Computer Socket (Cat5e), 1M	
289687	RJ45 Receptor, 1M (Suitable for AMPS, KRONE, Systimax Jack)	

Motor Starter Switch 240V~50Hz

289240	20A, Motor Starter Switch, 2M	
289241	25A, Motor Starter Switch, 2M	

Hospitality Range (240V~50Hz)

289431	Do Not Disturb Unit, 3M+2M	
289483	Bell Call Indicator, 1M	
289682	Neon Indicator (Red), 1M	
289286	Buzzer, 2M	
289327	Shaver Socket with Transformer, 110V/230V~ with 4M Cover and Inner Frame	
289420	20A, Key Card Unit with 30sec delay with 3M Cover and Inner Frame. (Supplied w/o Card)	
289326	Foot Light With Variable Shutter with 3M Cover & Inner Frame (White - Cool Day Light)	
289367	3M Foot Light with Variable Shutter - Warm White	

PLATES

288201	1 Module Plate	
288202	2 Module Plate	
288203	3 Module Plate	
288204	4 Module Plate	
288206	6 Module Plate	
288208	8 Module Plate (Square)	
288288	8 Module Plate (Horizontal)	
288209	9 Module Plate (Horizontal)	
288212	12 Module Plate	
288216	16 Module Plate	
288218	18 Module Plate	

Plates Dimensions

Module	1 M	2 M	3 M	4 M	6 M	8 M Horizontal	8 M Vertical	9 M	10 M	12 M	12 M Horizontal	16 M	18 M
ROMA PLUS													
X (mm)	94	94	118	146	220	260	146	260	NA	220	NA	260	220
Y (mm)	90	90	90	90	90	90	154	90	NA	154	NA	154	220

UNO Mini Modular MCB SP

89980	6A SP 'C' Mini MCB		89986	6A DP 'C' Mini MCB	
89981	10A SP 'C' Mini MCB		89987	10A DP 'C' Mini MCB	
89982	16A SP 'C' Mini MCB		89988	16A DP 'C' Mini MCB	
89983	20A SP 'C' Mini MCB		89989	20A DP 'C' Mini MCB	
89984	25A SP 'C' Mini MCB		89990	25A DP 'C' Mini MCB	
89985	32A SP 'C' Mini MCB		89991	32A DP 'C' Mini MCB	