

DX³ isolators

ISs for AC applications upto 125 A



DX³ RCCBs

RCCBs for AC applications upto 63 A



4065 00



4065 10



4065 20



4118 51



4118 77



4118 93



Technical characteristics **p. 53**

Isolators for AC applications upto 125 A

ISI marked as per IEC 60947-3

Integrated label holder

Ergonomic red color dolly

Sliding bottom clamp

Double break mechanism

Improved air channels

Color coded On/Off indication on dolly

Biconnect lower terminals

IP 20 protected terminals

Sliding shutters

Pack	Cat.Nos	Isolators	
		2 pole 415 V~	
		Nominal rating In (A)	Number of modules
1/5/60	4065 00	32	2
1/5/60	4065 01	40	2
1/5/60	4065 02	63	2
1/5/60	4065 04	100	2
1/5/60	4065 05	125	2
		3 pole 415 V~	
1/40	4065 09	32	3
1/40	4065 10	40	3
1/40	4065 11	63	3
1/40	4065 13	100	3
1/40	4065 14	125	3
		4 pole 415 V~	
1/32	4065 18	32	4
1/32	4065 19	40	4
1/32	4065 20	63	4
1/32	4065 22	100	4
1/32	4065 23	125	4



Technical characteristics **p. 54-59**

ISI marked as per IS 12640-1

Integrated label holder

Ergonomic Grey color dolly

Sliding bottom clamp

Color coded On/Off indication on dolly

Biconnect lower terminals

IP 20 protected terminals

35 sq mm terminals

Sliding shutters

Pack	Cat.Nos	DX³ RCCBs	
		2 pole 240 V~	
		30 mA	
		Nominal rating In (A)	Number of modules
1/5/60	4118 51	25	2
1/5/60	4118 52	40	2
1/5/60	4118 53	63	2
		100 mA	
1/5/60	4118 56	25	2
1/5/60	4118 57	40	2
1/5/60	4118 58	63	2
		300 mA	
1/5/60	4118 61	25	2
1/5/60	4118 62	40	2
1/5/60	4118 63	63	2
		4 pole 415 V~	
		30 mA	
1/32	4118 76	25	4
1/32	4118 77	40	4
1/32	4118 78	63	4
		100 mA	
1/32	4118 81	25	4
1/32	4118 82	40	4
1/32	4118 83	63	4
		300 mA	
1/32	4118 86	25	4
1/32	4118 87	40	4
1/32	4118 88	63	4
		4 pole 415 V~, A-S	
		300 mA	
1/5/60	4118 91	25	4
1/5/60	4118 92	40	4
1/5/60	4118 93	63	4
		2 pole 240 V~, HPI	
		30 mA	
1/5/60	4118 71	25	2
1/5/60	4118 72	40	2
1/5/60	4118 73	63	2
		4 pole 415 V~, HPI	
		30 mA	
1/32	4118 96	25	4
1/32	4118 97	40	4
1/32	4118 98	63	4

DX³ RCCBs

RCCBs for AC applications 80 - 100 A



DX³ RCB0s

RCB0s assembled for AC applications upto 63 A



4115 08



4117 05



4117 15



4113 24



4113 79



Technical characteristics p. 54-59

Integrated label holder
Ergonomic Grey color dolly
Color coded On/Off indication on dolly
IP 20 protected terminals
35 sq mm terminals
Sliding shutters
B type detect sinusoidal AC, pulsating DC and smooth DC residual currents



Technical characteristics p. 54-59

ISI marked as per IS 12640-2
Integrated label holder
Ergonomic design
Color coded On/Off indication on dolly
Front face indication for earth leakage fault
IP 20 protected terminals
35 sq mm terminals
Sliding shutters

Pack	Cat.Nos	DX ³ RCCBs*	
		2 pole 240 V~	
		30 mA	
1/5/60	4115 07	Nominal rating In (A) 80	Number of modules 2
1/5/60	4115 17	80	2
1/5/60	4115 27	80	2
		300 mA	
1/32	4117 05	80	4
1/32	4117 63	100	4
1/32	4117 15	80	4
1/32	4117 73	100	4
1/32	4117 25	80	4
1/32	4117 83	100	4
		4 pole 415 V~	
		30 mA	
1/32	4117 05	80	4
1/32	4117 63	100	4
1/32	4117 15	80	4
1/32	4117 73	100	4
1/32	4117 25	80	4
1/32	4117 83	100	4
		2 pole 240 V~, HPI	
		30 mA	
1/5/60	4118 74	80	2
		4 pole 415 V~, HPI	
		30 mA	
1/32	4118 99	80	4
		4 pole 415 V~, A-S	
		300 mA	
1/5/60	4118 94	80	4
		2 pole 230 V~, B type	
		Do not accept auxiliaries	
		30 mA	
1	4118 42	40	2
1	4118 43	63	2
		300 mA	
1	4118 44	40	2
1	4118 45	63	2
		4 pole 400 V~, neutral on left-hand side	
		B type	
		Do not accept auxiliaries	
		30 mA	
1	4118 46	40	4
1	4118 47	63	4
		300 mA	
1	4118 48	40	4
1	4118 49	63	4

*For industrial use only.

Pack	Cat.Nos	DX ³ RCB0s	
		2 pole 240 V~, AC Type	
		30 mA	
1/32	4113 22	Nominal rating In (A) 6	Number of modules 4
1/32	4113 23	10	4
1/32	4113 24	16	4
1/32	4113 25	25	4
1/32	4113 26	32	4
1/32	4113 27	40	4
1/32	4113 28	63	4
		100 mA	
1/32	4113 29	6	4
1/32	4113 30	10	4
1/32	4113 31	16	4
1/32	4113 32	25	4
1/32	4113 33	32	4
1/32	4113 34	40	4
1/32	4113 35	63	4
		300 mA	
1/32	4113 36	16	4
1/32	4113 37	25	4
1/32	4113 38	32	4
1/32	4113 39	40	4
1/32	4113 40	63	4
		4 pole 415 V~, AC Type	
		30 mA	
1/16	4113 88	6	7
1/16	4113 89	10	7
1/16	4113 65	16	7
1/16	4113 66	25	7
1/16	4113 67	32	7
1/16	4113 68	40	7
1/16	4113 69	63	7
		100 mA	
1/16	4113 70	16	7
1/16	4113 71	25	7
1/16	4113 72	32	7
1/16	4113 73	40	7
1/16	4113 74	63	7
		300 mA	
1/16	4113 75	16	7
1/16	4113 76	25	7
1/16	4113 77	32	7
1/16	4113 78	40	7
1/16	4113 79	63	7